

Declaration of Performance

No. 08-004-01

ALFAFIX[®] S11

Unique identification code of the product-type: 08-004

Intended use / intended uses: Rendering and plastering mortar

Producer: STOMIX, spol. s r.o.
Skorošice 197
790 65 Skorošice
Czech Republic

System / POSV systems: System 4

Harmonised standard: EN 998-1:2011
Specification for mortar for masonry – Part 1: Rendering and plastering mortar

Notified body / notified bodies: -

Declared property / declared properties:

Essential characteristics	Performance	Harmonised technical specification
Fire reaction class	F	EN 998-1:2011
Capillary water absorption	W1	EN 998-1:2011
Diffusion resistance factor	≤ 65	EN 998-1:2011
Adhesion	≥ 0.25 N/mm ²	EN 998-1:2011
Thermal conductivity	≤ 0.39 W/(m*k) pro P = 50% (predefined value)	EN 998-1:2011
	≤ 0.43 W/(m*k) pro P = 90% (predefined value)	EN 998-1:2011
Durability	NPD	EN 998-1:2011
Dangerous substances	NPD	EN 998-1:2011

Qualities of the above product are in conformity with a set of declared qualities. The Declaration of Performance is issued under the sole responsibility of the manufacturer specified above in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:


Skorošice, 3.7.2015



STOMIX, spol. s r. o.
790 65 Skorošice 197



Ing. David Čvanda, Development Production & Manager

	STOMIX, spol. s r. o. 790 65 Skorošice 197 Czech Republic ID: 48400874	
	15	08-004-01
EN 998-1:2011 Specification for mortar for masonry – Part 1: Rendering and plastering mortar		
Fire reaction class: F Capillary water absorption: W1 Diffusion resistance factor: ≤ 65 Adhesion: $\geq 0.25 \text{ N/mm}^2$ Thermal conductivity: $\leq 0.39 \text{ W/(m}\cdot\text{k)}$ pro P = 50% (predefined value) $\leq 0.43 \text{ W/(m}\cdot\text{k)}$ pro P = 90% (predefined value) Durability: NPD Dangerous substances: NPD		



WWW link