

# Declaration of Performance

No. 08-019-02

## BETAFIX<sup>®</sup> SF

Unique identification code of the product-type: 08-019

Intended use / intended uses: Adhesive designed for bonding ceramic tiles on walls and floors for indoor and outdoor use.

Producer: STOMIX, spol. s r. o.  
Skorošice 197  
790 65 Skorošice  
Czech Republic

System / POSV systems: System 3

Harmonised standard: EN 12004+A1:2012  
Adhesives for tiles  
– Requirements, evaluation of conformity, classification and designation

Notified body / notified bodies: The notified body Nr. 1301 – CPR 305/2011  
Výzkumný ústav pozemních staveb – Certifikační společnost, s.r.o.  
Pražská 810/16  
102 21 Praha 10 – Hostivař  
Czech Republic

Declared property / declared properties:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 12004+A1:2012
Initial adhesion	≥ 1.0 MPa	EN 12004+A1:2012
Adhesion after heat aging	≥ 1.0 MPa	EN 12004+A1:2012
Adhesion after immersion in water	≥ 1.0 MPa	EN 12004+A1:2012
Adhesion after freeze-thaw	≥ 1.0 MPa	EN 12004+A1:2012
Release of hazardous substances	See Safety Sheet	EN 12004+A1:2012
Open time	≥ 0.5 MPa not less than after 30 min.	EN 12004+A1:2012
Slip	≤ 0.5 mm	EN 12004+A1:2012

Qualities of the above product are in conformity with a set of declared qualities. The Declaration of Performance is issued under the sole responsibility of the manufacturer specified above in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Skorošice, 20.5.2015



**STOMIX, spol. s r. o.**  
790 65 Skorošice 197

Libuše Zichová, Quality Manager and EMS

	STOMIX, spol. s r. o. 790 65 Skorošice 197 Czech Republic ID: 48400874	
	07	08-019-02
EN 12004+A1:2012 Adhesives for tiles – Requirements, evaluation of conformity, classification and designation		
Reaction to fire: E Initial adhesion: $\geq 1.0$ MPa Adhesion after heat aging: $\geq 1.0$ MPa Adhesion after immersion in water: $\geq 1.0$ MPa Adhesion after freeze-thaw: $\geq 1.0$ MPa Release of hazardous substances: See Safety Sheet Open time: $\geq 0.5$ MPa not less than after 30 min. Slip: $\leq 0.5$ mm		



WWW link