

Declaration of Performance

No. 02-010-02

BETADEKOR® IF

Unique identification code of the product-type: 02-010

Intended use / intended uses: Manufactured exterior and interior render with organic binders used for exterior and interior render systems on walls, ceilings, pillars and partitions.

Producer: STOMIX, spol. s r. o.
Skorošice 197
790 65 Skorošice
Czech Republic

System / POSV systems: System 4

Harmonised standard: EN 15824:2009
Specifications for external renders and internal plasters based on organic binders

Notified body / notified bodies: -

Declared property / declared properties:

Essential characteristics	Performance	Harmonised technical specification
Water vapor permeability	V ₁	EN 15824:2009
Water absorption	W ₂	EN 15824:2009
Adhesion to concrete	0,3 MPa	EN 15824:2009
Durability	NPD	EN 15824:2009
Thermal conductivity	$\lambda = 0,8 \text{ W/(m.K)}$	EN 15824:2009
Reaction to fire	Euroclass C (consumption to 3,5 kg/m ²)	EN 15824:2009
	Euroclass F (consumption to 3,5 kg/m ²)	EN 15824:2009

Qualities of the above product are in conformity with a set of declared qualities. The Declaration of Performance is issued under the sole responsibility of the manufacturer specified above in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Skorošice, 20.5.2015


STOMIX, spol. s r. o.
790 65 Skorošice 197


Ing. David Čvanda, Development Production & Manager

	STOMIX, spol. s r. o. 790 65 Skorošice 197 Czech Republic ID: 48400874	
	11	02-010-02
EN 15824:2009 Specifications for external renders and internal plasters based on organic binders		
Water vapor permeability: V_1 Water absorption: W_2 Adhesion to concrete: 0,3 MPa Durability: NPD Thermal conductivity: $\lambda = 0,8 \text{ W/(m.K)}$ Reaction to fire: Euroclass C (consumption to 3,5 kg/m ²) Euroclass F (consumption to 3,5 kg/m ²)		



WWW link